
Meridian 1

QPC918 High Speed Data Card

Description, installation and operation

Document Number: 553-2731-108

Document Release: Standard 2.0

Date: December 1994

© 1993, 1994

All rights reserved

Printed in the United States of America

Information is subject to change without notice. Northern Telecom reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant. This equipment has been tested and found to comply with the limits for a Class A digital device pursuant to Part 15 of the FCC rules.

SL-1 and Meridian 1 are trademarks of Northern Telecom.

QPC918 High Speed Data Card

Revision history

August 10, 1990

Standard, release 1.0. Reissued for compliance with Northern Telecom standard 164.0.

December 31, 1992

Standard, release 2.0. This document was reissued to include technical content updates. Because of the extent of the changes, revision bars were not used.

December 1994

Standard, release 3.0. Reissued to include editorial changes and indexing. Due to the extent of the changes, revision bars are not used.

Contents

General information	1
Purpose	2
Features	2
Related documents	3
Functional description	5
Controls and indicators	5
Mode switches	7
Virtual Leased Line	7
SW2, SW4 definitions	8
SW1, SW3 definitions	9
Data Port Status lamps	9
Keyboard dialing	10
Interface specifications	13
Meridian 1 interface	13
RS-232 interface	13
V.35 interface	16
Data transmission rates	19
Data code and parity	21
Re-downline loading	21
Power requirements	22
Environmental	22

Reliability	22
Installation	23
Multi-Channel Data System (MCDS)	23
MCDS shelf to DTE connection	28
MCDS shelf to Meridian 1 connection	30
Service change	42
Troubleshooting	43

List of figures

Figure 1	
High Speed Data Card (HSDC) faceplate	6
Figure 2	
High Speed Data Card jumper locations	14
Figure 3	
MCDS QSD27 shelf	24
Figure 4	
MCDS power supply	25
Figure 5	
MCDS backplane (front view)	26
Figure 6	
MCDS backplane (rear view)	27
Figure 7	
MCDS to V.35 DTE connection	29
Figure 8	
MCDS shelf to host	31

List of tables

Table 1	
Data Port Status lamps	9
Table 2	
HSDC interface selection	15
Table 3	
EIA signals supported by the HSDC	15
Table 4	
V.35 (CCITT) signals supported by the HSDC and MCDS	17
Table 5	
Data transmission rates and switch settings	20
Table 6	
MCDS to SL-1 cabling	30
Table 7	
MCDS shelf pair-terminating sequence	32
Table 8	
QPC432 (4PDLC) and QPC311 DLC pair-terminations for NT8D13 PE Module I/O Panel connectors A, C, E, and G (Single Loop Mode) . . .	34
Table 9	
QPC432 (4PDLC) and QPC311 DLC pair-terminations for NT8D13 PE Module I/O Panel connectors B, D, and F (Single Loop Mode)	36
Table 10	
QPC432 (4PDLC) and QPC311 DLC pair-terminations for NT8D13 PE Module I/O Panel connectors A, C, E, and G (Single Loop Mode) . . .	38

Table 11
QPC432 (4PDLC) and QPC311 DLC pair-terminations for NT8D13 PE
Module I/O Panel connectors B, D, and F (Single Loop Mode) 40